

Section 1 - Chemical Product and Company Identification

1.1 Product/Chemical Name:

Product Form: Mixture
Product Name: SLIPS Tie Coat Part A
Product Code:
Formula: Unspecified
Synonyms: Unspecified
Chemical Family: Unspecified

1.2 Relevant identified uses of the substance or mixture and uses advised against

Use of substance/mixture Use for adhering anti-fouling lubricious surface to epoxy primer.
For professional use only.

1.3 Details of the supplier of the safety data sheet

SLIPS Technologies,
85 Bolton St
Cambridge MA, 02140
USA
Phone (617) 360-7080
info@slipstechnologies.com

1.4 Emergency telephone number

Emergency Number: INFOTRAC – 24/7 Emergency Response for Incidents During Transport
1-800-535-5053 (Inside U.S.) 1-352-323-3500 (Outside U.S.)

Section 2 - Hazards Identification

2.1 Classification of the substance or mixture

Classification (GHS-US)

Flam. Liq. 3, H226
Skin Irrit. 2, H315
Eye Irrit. 2, H319
STOT SE 3, H335

The product is classified as hazardous according to Regulation (EC) 1272/2008 as amended.

See Section 16 for the full text of the H statements declared above.

See Section 11 for more detailed information on health effects and symptoms.

2.2 Label elements

GHS-US labeling



Hazard Pictograms (GHS-US)

GHS02, GHS07

SLIPS Tie Coat Part A

Safety Data Sheet

Safety Data Sheet According to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Signal word (GHS-US)	Warning
Hazard statements (GHS-US)	Flammable liquid and vapor. Causes serious eye irritation. Causes skin irritation. May cause respiratory irritation.
Precautionary statements (GHS-US) :	Prevention: Wear protective gloves. Wear eye or face protection. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Use only outdoors or in a well-ventilated area. Response: IF INHALED: Remove person to fresh air and keep comfortable for breathing. IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower. IF ON SKIN: Take off contaminated clothing and wash it before reuse. Storage: Keep cool. Disposal: Dispose of contents and container in accordance with all local, regional, national, and international regulations.
Hazardous Ingredients:	Xylene, ethylbenzene
Supplemental Label Elements:	Wear appropriate respirator when ventilation is inadequate
2.3 Other Hazards	
Other hazards which do not result in classification:	None known.

Section 3 - Composition / Information on Ingredients

3.1 Substance

Not applicable

3.2 Mixture

Name	Product Identifier	%	Classification (GHS-US)
xylene	(CAS No) 1330-20-7	10 – 25	Flam. Liq. 3;H226 Acute Tox. 4;H332 Acute Tox. 4;H312 Skin Irrit. 2;H315 Eye Irrit. 2;H319 STOT SE 3;H335 Asp. Tox. 1;H304
ethylbenzene	(CAS No) 100-41-4	<5	Flam. Liq. 2;H225 Acute Tox. 4;H332 Asp. Tox. 1;H304 Eye Irrit. 2;H319 Skin Irrit. 2;H315 STOT SE 3;H335 STOT RE 2;H373

Full text of H-phrases: see section 16

SLIPS Tie Coat Part A

Safety Data Sheet

Safety Data Sheet According to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment, are PBTs or vPvBs or have been assigned a workplace exposure limit and hence require reporting in this section.

Section 4 - First Aid Measures

4.1 Description of first aid measures

General	In all cases of doubt, or when symptoms persist, seek medical attention. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and seek medical advice.
Inhalation	Remove to fresh air. Keep person warm and at rest. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel.
Skin Contact	In case of contact, immediately flush skin with soap and plenty of water. Get medical attention immediately
Eye Contact	Remove contact lenses, irrigate copiously with clean, fresh water, holding the eyelids apart for at least 10 minutes and seek immediate medical advice.
Ingestion	If swallowed, seek medical advice immediately and show the container or label. Keep person warm and at rest. Do NOT induce vomiting.

4.2 Most important symptoms and effects, both acute and delayed

Acute

Inhalation	May cause respiratory irritation
Skin	Causes skin irritation.
Eyes	Causes serious eye irritation.
Ingestions	Irritating to mouth, throat and stomach.

Over-exposure signs/symptoms

Eyes	Pain or irritation, watering, redness
Inhalation	Respiratory tract irritation, coughing, headache, drowsiness/fatigue, dizziness/vertigo, muscle weakness, unconsciousness
Skin Contact	Irritation, redness
Ingestion	No specific data

4.3 Indication of any immediate medical attention and special treatment needed

Notes to physician	Treat symptomatically. Contact poison treatment specialist immediately if large quantities have been ingested or inhaled.
Specific Treatments	No specific treatment.

Section 5 - Fire-Fighting Measures

5.1 Extinguishing media

Suitable Extinguishing media: Use dry chemical, CO₂, water spray (fog) or foam.

Unsuitable extinguishing media: Do not use water jet.

5.2 Special hazards arising from the substance or mixture

Hazards from the substance or mixture Flammable liquid and vapor. In a fire or if heated, a pressure increase will occur and the container may burst, with the risk of a subsequent explosion. Runoff to sewer may create fire or explosion hazard.

SLIPS Tie Coat Part A

Safety Data Sheet

Safety Data Sheet According to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Hazardous thermal decomposition products	Decomposition products may include the following materials: carbon dioxide, carbon monoxide, metal oxide/oxides
5.3 Advice for firefighters	
Special protective actions for fire-fighters	Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training. Move containers from fire area if this can be done without risk. Use water spray to keep fire-exposed containers cool.
Special protective equipment for fire-fighters	Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode. Clothing for fire-fighters (including helmets, protective boots and gloves) conforming to European standard EN 469 will provide a basic level of protection for chemical incidents.
Section 6 - Accidental Release Measures	
6.1 Personal precautions, protective equipment and emergency procedures	
For non-emergency personnel	No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Shut off all ignition sources. No flares, smoking or flames in hazard area. Avoid breathing vapour or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.
For emergency responders	If specialised clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".
6.2 Environmental precautions	
Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).	
6.3 Methods and material for containment and cleaning up	
Small spill	Stop leak if without risk. Move containers from spill area. Use spark-proof tools and explosion-proof equipment. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.
Large spill	Stop leak if without risk. Move containers from spill area. Use spark-proof tools and explosion-proof equipment. Approach the release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with noncombustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations. Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilled product.

SLIPS Tie Coat Part A

Safety Data Sheet

Safety Data Sheet According to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Section 7 - Handling and Storage

7.1. Precautions for safe handling

Protective measures Put on appropriate personal protective equipment (see Section 8). Do not ingest. Avoid contact with eyes, skin and clothing. Avoid breathing vapour or mist. Use only with adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Do not enter storage areas and confined spaces unless adequately ventilated. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Store and use away from heat, sparks, open flame or any other ignition source. Use explosion-proof electrical (ventilating, lighting and material handling) equipment. Use only non-sparking tools. Take precautionary measures against electrostatic discharges. Empty containers retain product residue and can be hazardous. Do not reuse container.

Advice on general occupational hygiene Eating, drinking, and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.

7.2. Conditions for safe storage, including any incompatibilities

Store in accordance with local regulations. Store in a segregated and approved area. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Store locked up. Eliminate all ignition sources. Vapors are heavier than air and may spread along floors. Separate from oxidizing materials. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabelled containers. Use appropriate containment to avoid environmental contamination.

7.3. Specific end use(s)

Recommendations: Not available.

Industrial sector specific solutions: Not available.

Section 8 - Exposure Controls / Personal Protection

8.1 Control parameters

Occupational exposure limits

Product/Ingredient name	Exposure limit values
Xylene	EH40/2005 WELs (United Kingdom (UK), 12/2011). Absorbed through skin. STEL: 441 mg/m ³ 15 minutes. STEL: 100 ppm 15 minutes. TWA: 220 mg/m ³ 8 hours. TWA: 50 ppm 8 hours.

SLIPS Tie Coat Part A

Safety Data Sheet

Safety Data Sheet According to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Ethylbenzene	EH40/2005 WELs (United Kingdom (UK), 12/2011). Absorbed through skin. STEL: 552 mg/m ³ 15 minutes. STEL: 125 ppm 15 minutes. TWA: 441 mg/m ³ 8 hours. TWA: 100 ppm 8 hours.
Recommended monitoring Procedures	If this product contains ingredients with exposure limits, personal, workplace atmosphere or biological monitoring may be required to determine the effectiveness of the ventilation or other control measures and/or the necessity to use respiratory protective equipment. Reference should be made to monitoring standards, such as the following: European Standard EN 689 (Workplace atmospheres - Guidance for the assessment of exposure by inhalation to chemical agents for comparison with limit values and measurement strategy) European Standard EN 14042 (Workplace atmospheres - Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents) European Standard EN 482 (Workplace atmospheres - General requirements for the performance of procedures for the measurement of chemical agents) Reference to national guidance documents for methods for the determination of hazardous substances will also be required.
DNELs/DMELs PNECs	No DNELs/DMELs available. No PNECs available
8.2 Exposure controls Appropriate engineering controls	Use only with adequate ventilation. Use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits. The engineering controls also need to keep gas, vapor or dust concentrations below any lower explosive limits. Use explosion-proof ventilation equipment.
Individual protection measures Hygiene measures	Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.
Eye/face protection	Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to

SLIPS Tie Coat Part A

Safety Data Sheet

Safety Data Sheet According to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Skin protection

Hand protection

avoid exposure to liquid splashes, mists, gases or dusts. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: chemical splash goggles.

Use chemical resistant gloves classified under Standard EN 374: Protective gloves against chemicals and micro-organisms. Recommended: Viton® or Nitrile gloves. When prolonged or frequently repeated contact may occur, a glove with a protection class of 6 (breakthrough time greater than 480 minutes according to EN 374) is recommended. When only brief contact is expected, a glove with a protection class of 2 or higher (breakthrough time greater than 30 minutes according to EN 374) is recommended. The user must check that the final choice of type of glove selected for handling this product is the most appropriate and takes into account the particular conditions of use, as included in the user's risk assessment. NOTICE: The selection of a specific glove for a particular application and duration of use in a workplace should also take into account all relevant workplace factors such as, but not limited to: Other chemicals which may be handled, physical requirements (cut/puncture protection, dexterity, thermal protection), potential body reactions to glove materials, as well as the instructions/ specifications provided by the glove supplier. Barrier creams may help to protect the exposed areas of the skin but should not be applied once exposure has occurred.

Body Protection

Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product. When there is a risk of ignition from static electricity, wear anti-static protective clothing. For the greatest protection from static discharges, clothing should include anti-static overalls, boots and gloves. Refer to European Standard EN 1149 for further information on material and design requirements and test methods.

Other skin protection

Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

Respiratory protection

Use a properly fitted, air-purifying or air-fed respirator complying with an approved standard if a risk assessment indicates this is necessary. Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator.

SLIPS Tie Coat Part A

Safety Data Sheet

Safety Data Sheet According to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Environmental exposure controls	Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.
---------------------------------	--

Section 9 - Physical and Chemical Properties

9.1. Information on basic physical and chemical properties

Appearance

Physical State	Liquid
Color	Red
Odor	Solvent
Odor threshold	Not Measured
pH	Not applicable
Evaporation Rate	Not Measured
Melting point	Not Measured
Freezing point	Not Measured
Boiling point and boiling range	136.16 (°C), 277.1(°F)
Flash point	Closed cup 28 (°C)
Auto-ignition Temperature	Not Measured
Decomposition temperature	Not Measured
Flammability (solid, gas)	Not Applicable
Vapor pressure	Not Measured
Relative density	1.36
Specific Gravity	Not Measured
Solubility	Insoluble in cold water
Viscosity	Kinematic (room temperature): 1471 mm ² /s

9.2 Other information

No additional information

Section 10 - Stability and Reactivity

10.1 Reactivity

No specific test data related to reactivity available for this product or its ingredients.

10.2 Chemical stability

The product is stable.

10.3 Possibility of hazardous reactions

Under normal conditions of storage and use, hazardous reactions will not occur.

10.4 Conditions to avoid

Avoid all possible sources of ignition (spark or flame). Do not pressurize, cut, weld, braze, solder, drill, grind or expose containers to heat or sources of ignition.

10.5 Incompatible materials

oxidizing materials

10.6 Hazardous decomposition products

SLIPS Tie Coat Part A

Safety Data Sheet

Safety Data Sheet According to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Under normal conditions of storage and use, hazardous decomposition products should not be produced.

Section 11- Toxicological Information**Acute Toxicity**

Ingredient	Result	Species	Dose	Exposure
Xylene	LD50 Oral	Rat	4300 mg/kg	-
Ethylbenzene	LC50	Rabbit	4000 ppm	4 hours
	Inhalation Gas			
	LD50 Dermal	Rabbit	17800 mg/kg	-
	LD50 Oral	Rat	3500 mg/kg	-

Acute toxicity estimates

Route	ATE value
Dermal	5504.1 mg/kg
Inhalation (vapors)	44.03 mg/l

Irritation/Corrosion

Product/Ingredient Name	Result	Species	Score	Exposure	Observation
Ethylbenzene	Eyes- severe irritant	Rabbit	-	500 milligrams	-
	Skin- Mild irritant	Rabbit	-	24 hours 15 milligrams	-

Specific target organ toxicity (single exposure)

Product/Ingredient Name	Category	Route of exposure	Target organs
Xylene	3	Not applicable	Respiratory tract irritation
Ethylbenzene	3	Not applicable	Respiratory tract irritation

Specific target organ toxicity (repeated exposure)

Product/ingredient name	Category	Route of exposure	Target organs
Ethylbenzene	2	Not determined	Hearing organs

Aspiration Hazard

Product/ingredient name	Result
Xylene	ASPIRATION HAZARD – Category 1
Ethylbenzene	ASPIRATION HAZARD – Category 1

Potential acute health effects

Eye contact Causes serious eye irritation

SLIPS Tie Coat Part A

Safety Data Sheet

Safety Data Sheet According to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Inhalation May cause respiratory irritation
Skin contact Causes skin irritation
Ingestion Irritating to mouth, throat, and stomach

Symptoms related to the physical, chemical, and toxicological characteristics

Eye contact Pain or irritation
Watering
Redness
Inhalation Respiratory tract infection
Coughing
Headache
Drowsiness/fatigue
Dizziness/vertigo
Muscle weakness
Unconsciousness
Skin contact Irritation
Redness
Ingestion No specific data

Potential Chronic Health Effects

There are no know significant chronic effects or critical hazards

Section 12 - Ecological Information

12.1 Toxicity

No additional information provided for this product. See Section 3 for chemical specific data

Product/Ingredient name	Result	Species	Exposure
Xylene	Acute LC50 8500 µg/l Marine water	Crustaceans - Palaemonetes pugio	48 hours
	Acute LC50 13400 µg/l Fresh water	Fish - Pimephales promelas	96 hours
Ethylbenzene	Acute EC50 3.6 mg/l Fresh water	Algae - Pseudokirchneriella subcapitata	96 hours
	Acute LC50 18.4 to 25.4 mg/l Fresh water	Daphnia - Daphnia magna - Neonate	48 hours
	Acute LC50 5.1 to 5.7 mg/l Marine water	Fish - Menidia menidia	96 hours

12.2 Persistence and degradability

SLIPS Tie Coat Part A

Safety Data Sheet

Safety Data Sheet According to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Product/Ingredient name	Aquatic half-life	Photolysis	Biodegradability
Ethylbenzene	-	-	Readily

12.3 Bioaccumulative potential

Product/ingredient name	LogP _{ow}	BCF	Potential
Xylene	3.12	8.1 to 25.9	Low
Ethylbenzene	3.6	15	Low

12.4 Mobility in soil

No data available

12.5 Results of PBT and vPvB assessment

Not applicable

12.6 Other adverse effects

No known significant effects or critical hazards

Section 13 – Disposal considerations

13.1 Waste treatment methods

Product

Methods of disposal

The generation of waste should be avoided or minimized wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements.

Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction.

Hazardous waste

The classification of the product may meet the criteria for a hazardous waste

Packaging

Methods of disposal

This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Vapor from product residues may create a highly flammable or explosive atmosphere inside the container. Do not cut, weld or grind used containers unless they have been cleaned thoroughly internally. Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers.

SLIPS Tie Coat Part A

Safety Data Sheet

Safety Data Sheet According to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Section 14 – Transport information

In accordance with DOT / IMDG / IATA

14.1 UN number

UN 1263

14.2 UN proper shipping name

Paint

14.3 Transport Hazard Class(es)

DOT (Domestic Surface Transportation)

DOT Proper Shipping Name	Paint
DOT Hazard Class	3 – Flammable
UN/NA Number	Un 1263
DOT Packing Group	III

IMO / IMDG (Ocean Transport)

IMDG Proper Shipping Name	Paint
IMDG Hazard Class	3 – Flammable
Sub Class	3 – Flammable
IMDG Packing Group	III
System Reference Code	1

14.4 Packing Group III

14.5 Environmental Hazards

No

14.6 Special precautions for user

Transport within user's premises: always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

14.7 Transport in bulk in accordance to Annex II of MARPOL73/78 and the IBC Code

Not Applicable

Section 15 – Regulatory information

15.1 Safety, health, and environmental regulations/legislation specific for the substance or mixture

EU Regulation (EC) No. 1907/2006 (REACH)

Annex XIV – List of substances subject to authorization

Annex XIV

Substances of very high concern

None of the components are listed.

Annex XVII – Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles

Not applicable

Special packaging requirements

Not applicable

Ozone depleting substances (1005/2009/EU)

SLIPS Tie Coat Part A

Safety Data Sheet

Safety Data Sheet According to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Not listed

Prior Informed Consent (PIC) (649/2012/EU)

Not listed

Section 16 – Other information

Revision date

4/9/2018

Abbreviations and acronyms

ATE = Acute Toxicity Estimate

CLP = Classification, Labelling and Packaging Regulation
[Regulation (EC) No. 1272/2008]

DMEL = Derived Minimal Effect Level

DNEL = Derived No Effect Level

EUH statement = CLP-specific Hazard statement

PBT = Persistent, Bioaccumulative and Toxic

PNEC = Predicted No Effect Concentration

RRN = REACH Registration Number

vPvB = Very Persistent and Very Bioaccumulative

Classification	Justification
Flam. Liq. 3, H226	On basis of test data
Skin Irrit. 2, H315	Calculation method
Eye Irrit. 2, H319	Calculation method
STOT SE 3, H335	Calculation method

Full text of abbreviated H statements

H225	Highly flammable liquid and vapor
H226	Flammable liquid and vapor
H304	May be fatal if swallowed and enters airways
H312	Harmful in contact with skin
H315	Causes skin irritation
H319	Causes serious eye irritation
H332	Harmful if inhaled
H335	May cause respiratory irritation
H373 (hearing organs)	May cause damage to organs through prolonged or repeated exposure (hearing organs)

Full text of classifications

Acute tox. 4, H312	ACUTE TOXICITY (dermal) – Category 4
Acute tox. 4, H332	ACUTE TOXICITY (inhalation) – Category 4
Asp. Tox. 1, H304	ASPIRATION HAZARD – Category 1
Eye Irrit. 2, H319	SERIOUS EYE DAMAGE/ EYE IRRITATION – Category 2
Flam. Liq. 2, H225	FLAMMABLE LIQUIDS – Category 2
Flam. Liq. 3, H226	FLAMMABLE LIQUIDS – Category 3
Skin Irrit. 2, H315	SKIN CORROSION/IRRITATION – Category 2
STOT RE 2, H373 (hearing organs)	SPECIFIC TARGET ORGAN TOXICITY (REPEATED EXPOSURE) (hearing organs) – Category 2

SLIPS Tie Coat Part A

Safety Data Sheet

Safety Data Sheet According to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

STOT SE 3, H335

SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE)
(Respiratory tract irritation) – Category 3

End of Document

SDS US (GHS HazCom 2012) - US